

Asbestos rubber sheet



Other name in world : Asbestos Jointing Sheet,
Compressed Asbestos Fiber Jointing Sheet,
CAF Gasket Sheet,
Asbestos Sheet,
Asbestos Jointing
Paronite,

Made of asbestos Fibre, rubber and heat-resisting packing material, compressing it to thick paper .Used for the equipment in water,steam,etc.and used as sealing material in the joints of pipeline.

This series include: XB150,XB200,XB250,XB300,XB350,XB400,XB450,XB510.

With steel wire inserted and coated with graphite on the surface is applicable

Available Sizes:

Thickness: 0.3 to 6mm

4500 x 1500mm, 4100 x 1500 mm, 3850 x 1300 mm, 3810 x 2700 mm

1500 x 2000 mm, 1500 x 1500 mm , 1500 x 1350 mm, 1500 x 1000 mm ,

1270 x 1270 mm,

The other size is optional or according to the requirements of customers.

Packing: in roll or in wooden pallet of about 1000 kgs, 2000kgs net each.

Products data sheet

GB/T 3985---2008

Item	XB510	XB450	XB400	XB350	XB300	XB250	XB200	XB150	
Tensile strength MPa \geq	21	19.0	15.0	12.0	9.0	7.0	6.0	5.0	
Burning Loss % \leq	28			30					
Compressibility %	7 ~ 17								
Rebound degree	45			40			35		
Creep Stress-relaxation \leq	50								
Aging Coefficient \geq	0.9								
Density g/cm ³	1.9 ~ 2.0								
Normal temperature Pliability	Bend 180 degree on the round column (the column diameter is 12 multiple sample thickness), No crack								
Nitrogen leakage rate [(ml/h.mm)] \leq	500								
Steam Airtightness	Temperature $^{\circ}$ C	500~510	440~450	390~400	340~350	290~300	240~250	190~200	140~150
	Steampressure MPa	13~14	11~12	8~9	7~8	4~5	3~4	2~3	1.5~2
	Request	Keep for 30 minutes without Leakage							