


Acid-resisting asbestos rubber sheet



Made of asbestos fiber and acid-resisting synthetic rubber and heat-resisting packing material, compressing it to thick paper .

Mainly used for the equipment in acid, and used as sealing material of gasket for the flange of pipeline joints.

The series include: NS250, NS350, NS450

Available Sizes:

Thickness: 0.5 to 6mm

**4500 x 1500mm, 4100 x 1500 mm, 3850 x 1300 mm, 1500 x 2000 mm,
1500 x 1500 mm , 1500 x 1350 mm, 1500 x 1000 mm , 1270 x 1270 mm,**

The other size is optional or according to the requirements of customers.

Packing: in roll or in wooden pallet of about 1000 kgs, 2000kgs net each.

Products data sheet

Item		NS450	NS350	NS250
Tensile strength MPa \geq		14	11	8
Weight-increasing	96.17%(H ₂ SO ₄) =18mol/L*48h	\leq 45%	\leq 40%	\leq 30%
	36.97%(HCL)=12mol/L*48h	\leq 45%	\leq 35%	\leq 25%
	10% (H _N O ₃)= 1.67mol/L*48h	\leq 40%	\leq 30%	\leq 20%
Max. Pressure Mpa		4.0	3.0	2.0
Max. Temperature $^{\circ}$ C		450	350	250
Strain-decreasing % \leq		50		
Aging Coefficient		0.9		
Softness		No Crack		
Density g/cm ²		1.9-2.1		
Burning Loss %		30		
Compressibility		12 \pm 5		
Elasticity \geq %		40		